

V4




BEFORE USE OF VENDLET V4

1. The bars must be raised and the surface of the bed must be flat and horizontal before operating VENDLET. Adjust the height of the bed to ensure correct posture when removing the side rails.
2. Remove the side rails and hang them on the supports for side rails beneath the bars.
3. Turn to release the stop button to turn on the power supply.
4. Press the green start button to activate the timer for 1½ minutes.
5. VENDLET is ready for use. If the timer disconnects while VENDLET is in use, press the green start button to reactivate the timer.

AFTER USE OF VENDLET V4

1. Raise the bars to top level.
2. Slacken the turning sheet on both bars and adjust the height of the bed. Press the side rails on to the bars.
3. Press the red stop button to cut off the power supply.



Always press the red stop button to turn off the power supply after use of VENDLET.



Always direct full attention on the patient when using VENDLET.

VENDLET must be mounted and operated as described in the user manual.





MOUNTING OF SLIDE SHEET

The slide sheet reduces the friction against the mattress and thereby the electricity consumption when using VENDLET.



1. Stretch the elastic in the corners of the slide sheet round the mattress.
2. Guide the velcro straps round the steel frame under the mattress.

MOUNTING OF TURNING SHEET

1. Place the turning sheet in the middle of the bed with the central red line face up.
2. Fasten the turning sheet to the velcro straps on the bars at the same distance from the ends on both sides. The sheet must always roll OVER the bars. If the turning sheet rolls up from under the bars this will reduce the tractive force. Do not pull the sheet as it will fit exactly on the bar.
3. Turn to release the stop button and press the green start button to activate the timer (the timer is active for 1½ minutes).
4. Tighten the turning sheet firmly on the bars using  and , so that it rises above the mattress.
5. Loosen the sheet again. Make sure that the sheet lies smoothly with the red line in the centre of the bed.

SIDE RAILS

The side rails are to hang securely between the mattress and the support on the inner side of the bar. Use 2 side rails on each bar:

1. Press  and  to slacken the sheet on both bars enough to allow for the side rails to be pressed on to the bars.
2. Adjust the height of the bed to ensure correct posture. When the side rails are pressed on to the bars, the spacer at the bottom of the side rail must be in line with the head- or footboard. Always attach the side rail at the foot of the bed before the side rail at the head of the bed.
3. Always hang the side rails on the supports for side rails beneath the bars when they are not in use.



The easiest way to attach the side rails is to press the bent edges on to the bars one at a time.



To remove the side rails take hold of the side and pull upwards.